

FWDCEL[®] MP 150M

Hydroxypropyl Methyl Cellulose

FWDCEL[®] MP 150M is an unmodified construction use Hydroxypropyl Methyl Cellulose. It is white flowing powder with good water solubility. It has thickening ability, high purity, PH stability, high water retention, excellent film forming, better workability and a wide range of slip resistance, dispersion and adhesion.

Technical Data

| Property | Value | Unit |
|---|---------------------------------|-------|
| Physical form | White powder | |
| Moisture | Max. 6.0 | % |
| Ash content | Max. 5.0 | % |
| Bulk density | 0.30-0.50g/cm ³ | |
| PH | 4.0-8.0 | % |
| Particle Size | min.92% pass through 80 mesh | |
| Viscosity, (Brookfield RV, 2% solution (20°C)) | 55,000-65,000 | mPa.s |

Applications

- Tile adhesive ·Cement/Gypsum based skim coat ·Dry-mixed plastering mortar
- Masonry mortar ·External Wall Insulation Mortar

Packaging

25kg multi-layer paper bags with an inner polyethylene bag.
20'FCL:12 tons with pallets or 14 tons without pallets.
(Refer to the actual grade for specific data)

Storage and Shelf Life

2 years under cool, dry conditions in original packaging away from heat sources.
It is recommended to use the product in rotation on a first-in first-out basis.