



SHANDONG FORWARD NEW MATERIAL TECHNOLOGY CO., LTD.  
No. 1166, Xinluo Street, Pilot Free Trade Zone, Jinan City, Shandong, China  
Email: info@fwdnewtech.com  
www.fwdnewtech.com

## FWDCEL<sup>®</sup> MP 15M Hydroxypropyl Methyl Cellulose

FWDCEL<sup>®</sup> MP 15M is a low viscosity construction grade hydroxypropyl methyl cellulose.

It is white flowing powder with good water solubility.

It has thickening ability, high purity, pH stability, high water retention, better workability and a wide range of slip resistance, dispersion and adhesion.

### Technical Data

Property	Value	Unit
Physical form	White powder	
Moisture	Max. 6.0	%
Ash content	Max. 5.0	%
Bulk density	0.30-0.50g/cm <sup>3</sup>	
PH	4.0-8.0	%
Particle Size	min.92% pass through 80 mesh	
Viscosity, (Brookfield RV, 2% solution (20°C))	15,000-25,000	mPa.s

### Applications

- Gypsum plaster
- Gypsum based skim coat
- Masonry mortar
- External Wall Insulation Mortar

### Packaging

25kg multi-layer paper bags with an inner polyethylene bag.

20'FCL:12 tons with pallets or 14 tons without pallets.

(Refer to the actual grade for specific data)

### Storage and Shelf Life

2 years under cool, dry conditions in original packaging away from heat sources.

It is recommended to use the product in rotation on a first-in first-out basis.

