

# FWDCEL<sup>®</sup> MP 200EX

## Hydroxypropyl Methyl Cellulose

FWDCEL<sup>®</sup> MP 200EX is a modified construction use Hydroxypropyl Methyl Cellulose. It is white flowing powder with good water solubility, thickening ability, high water retention, It is good to extend the open time, improve workability.

### Technical Data

Property	Value	Unit
Physical form	White powder	
Moisture	Max. 6.0	%
Ash content	Max. 5.0	%
Bulk density	0.30-0.50g/cm <sup>3</sup>	
PH	4.0-8.0	%
Particle Size	min.92% pass through 80 mesh	
Viscosity, (Brookfield RV, 2% solution (20°C))	70,000-80,000	mPa.s

### Applications

- Tile adhesive      ·Cement/Gypsum based skim coat      ·Dry-mixed plastering mortar
- Masonry mortar    ·External Wall Insulation Mortar

### Packaging

25kg multi-layer paper bags with an inner polyethylene bag.  
20'FCL:12 tons with pallets or 14 tons without pallets.  
(Refer to the actual grade for specific data)

### Storage and Shelf Life

2 years under cool, dry conditions in original packaging away from heat sources.  
It is recommended to use the product in rotation on a first-in first-out basis.